
TECHNICAL SPECIFICATION			
Overall dimension		mm	16,740 x 3,330 x 3,090
Wheelbase		mm	12,110 + 1,220 + 1,220
Tare weight		kg	13,000
Design pay load		kg	43,000
Design total mass		kg	56,000
Main beam dimension		mm	Welded beam 520/180
Axle			FUWA 13 tons
Kingpin			3.5" (ø90), bolted connection
Landing gear			FUWA 28 tons
Twist locks			10
Suspension system	Spring hanger		Mechanical Suspension – FUWA
	Leaf spring		10 leaf springs (90x13 mm)
Control valve			WABCO
Brake system			Locked on 3 axles
Electrical system			10 – 30V (suitable for all tractor types)
Tire size			285/70R19.5
Painting technology			Shot blasting SA 2.5 Primer Topcoat
Paint color (upon request)			Blue (standard color)

The product is covered by a 36-month warranty (details outlined in the accompanying warranty booklet) and can be serviced at any authorized THACO AUTO dealership nationwide.



DURABLE - SAFE - ECONOMICAL

Thaco Trailers continuously invests in advanced technologies to create superior and reliable products.



Modern design, advanced manufacturing technology, high-strength alloy steel material, solid structure, increased load capacity with high stability.



AXLE

FUWA 13-ton axle.



SUSPENSION SYSTEM

The suspension system uses 10 leaf springs system with high durability and large load capacity, ensuring smooth operation.



ELECTRICAL SYSTEM

High-quality LED lighting system capable of withstanding harsh weather conditions, using 10-30V power source compatible with all types of tractors.



TIRES

Uses 285/70R19.5 tires.



BRAKE SYSTEM

3-axle air brake system with WABCO splitter valve to help prevent tire slippage when braking, ensuring safe operation.




CHÂN CHỐNG


FUWA landing gear with a dynamic load capacity of 28 tons and a static load capacity of 80 tons, helps to effectively distribute weight, preventing excessive pressure on each structure of the semi-trailer.





DIMENSIONS





CARGO CAPACITY





